Largo

Architectural Profile



Also Available in:



corelli

Architectural profile manufactured from AL6063 type aluminium fitted with UV stabilised PMMA diffusers.

Suitable for surface mount accent and task light applications. May be recessed for a trimless look. Wide build especially suited for joinery task and up-lighting.

Recommended for LED types up to 20mm wide and up to 20W/m output (30W/m if surface mounted with clips).

Supplied made to measure, fitted with all accessories and drivers as required. Configured to suit most dimming protocols.

			Suggested		es:		
			3528-120-10				
RECESSED	CLEAR DIFFUSER		3528-180-15				
		120'	5050-120-24		11		
			2835-120-10				
	FROSTED	140'	2835-120-24		11		
			2835-180-18				
			2110-700-20				(()))))))))))))))))))))))))))))))))))))
	OPAL DIFFUSER	160*			0	20.6	ACTUAL
Please	contact u	s for specification coc	les to match your sele	ctions.	Some details on profiles may change without notice.	25.2	

CORELLI LIGHTING CONCEPTS PTY LTD | 68 LAMBECK DVE, TULLAMARINE VIC. 3043 | TEL: 03 9338 9337 | FAX: 03 9338 9937 | MOB: 0419 586 561 | WEB: WWW.CORELLI.COM.AU | EMAIL: SALES@CORELLI.COM.AU